





DF6A



PACKED WITH FEATURES







- Compact and lightweight, easy to transport and deliver surprising low and mid range torque for quick acceleration.
- Effortless control.
- Large carry handle gives excellent portability.

MODEL	DF6A
RECOMMENDED TRANSOM HEIGHT mm	S:381, L:508
STARTING SYSTEM	Manual
WEIGHT kg *5	\$:24, L:25
ENGINE TYPE	OHV
FUEL DELIVERY SYSTEM	Carburetor
NO. OF CYLINDERS	1
PISTON DISPLACEMENT cm ³	138
BORE ×STROKE mm	60.4 X 48
MAXIMUM OUTPUT kW	4,4
FULL THROTTLE OPERATING RANGE rpm	4,750-5.750
STEERING	Tiller
СНОКЕ	Manual
OIL PAN CAPACITY Lit.	0.7
FUEL TANK CAPACITY Lit.	Integral 1.0
IGNITION SYSTEM	Digital CDI
ALTERNATOR	12V 5A (Option)
ENGINE MOUNTING	Bushing Type
TRIM METHOD	Manual Trim and Tilt
GEAR RATIO	1.92:1
GEAR SHIFT	F-N-R
EXHAUST	Above Prop Exhaust
PROPELLER SELECTION (Pitch) *6 All propellers are the 3-blade type	6"-7"